owers







PRODUCT INFO

- Self-draining shower valves
- Free standing models
- Separate modules
- Easy maintenance
- Compact packaging
- Cost effective carriage

TECHNICAL DETAILS

 Available with tubulars either of galvanised carbon steel protected by green Hammerite enamel, or alternatively of semi-polished stainless steel

CHOICES

- Body spray
- Eyebath and Facewash units

Galvanised	Stainless Steel	Depth mm	Width mm	Height mm	Weight kg	Inlet Size (" inches) BSP	Min. Pressure kg/cm² (bar g)	Water Flow I/min
Self-draining show	vers							
EXP-SD-18G	EXP-SD-18GS	750	425	2260	15	11/4"	1.8	75
EXP-SD-20G	EXP-SD-20GS	750	425	2260	16	11/4"	1.8	115
EXP-SD-18G/45G	EXP-SD-18GS/45G	750	520	2260	18	11/4"	2	75
EXP-SD-18G/25K	EXP-SD-18GS/25KS	750	570	2260	25	11/4"	2.2	75
EXP-SD-20G/45G	EXP-SD-20GS/45G	1180	550	2260	19	11/4"	2	115
EXP-SD-20G/25K	EXP-SD-20GS/25KS	1390	550	2260	26	11/4"	2.2	115