



## EXP-EH-5G/34G

Emergency Safety Shower with Eye/Facewash Diffusers, trace tape heated and pre-insulated. Available in Galvanised or Stainless Steel.

**EXP-AH-5G/34G** extra heating.  
**EXP-EJ-5G/34G** insulated only.

### OPTIONAL FITTINGS:

- Signs and Brackets
- Treadle Foot Control for eye/facewash
- Light
- Light Box
- Proximity Switches
- Underground Extension Pipe
- Cubicle



## EXP-EH-5G/35G

Emergency Safety Shower with Eyebath on flexible hose, trace tape heated and pre-insulated. Available in Galvanised or Stainless Steel.

**EXP-AH-5G/35G** extra heating.  
**EXP-EJ-5G/35G** insulated only.

### OPTIONAL FITTINGS:

- Signs and Brackets
- Treadle Foot Control for eyebath
- Light
- Light Box
- Proximity Switches
- Underground Extension Pipe
- Cubicle



## EXP-EH-5G/45G

Emergency Safety Shower with Eye/Facewash Fountain, trace tape heated and pre-insulated. Available in Galvanised or Stainless Steel.

**EXP-AH-5G/45G** extra heating.  
**EXP-EJ-5G/45G** insulated only.

### OPTIONAL FITTINGS:

- Signs and Brackets
- Treadle Foot Control for eye/facewash
- Light
- Light Box
- Proximity Switches
- Underground Extension Pipe
- Cubicle

## PRODUCT INFO

- Heated versions for use in cold climates
- Insulated versions for use in hot climates
- Arctic versions with extra heating for very cold climates
- Wall mounted models
- Free standing models

## TECHNICAL DETAILS

- Modular design
- Easy maintenance
- Self-draining removable spray nozzles free from build up of bacteria
- Compact packaging
- Cost effective carriage

## CHOICES

- Available in Galvanised or Stainless Steel

Galvanised	Stainless Steel	Depth mm	Width mm	Height mm	Weight kg	Inlet Size (" inches) BSP	Min. Pressure kg/cm <sup>2</sup> (bar g)	Water Flow l/min
<b>Heated Emergency Showers</b>								
EXP-EH-2G	EXP-EH-2GS	930	230	230	26	1"	1.5	75
EXP-EH-45G/P	EXP-EH-45GS/P	500	340	1180	26	1 1/4"	2	20
EXP-EH-5G	EXP-EH-5GS	850	150	2310	30	1 1/4"	1.5	75
EXP-EH-5G/10G	EXP-EH-5GS/10GS	850	460	2310	32	1 1/4"	1.8	115
EXP-EH-5G/34G	EXP-EH-5GS/34GS	850	300	2310	32	1 1/4"	2.2	75
EXP-EH-5G/35G	EXP-EH-5GS/35GS	850	240	2310	32	1 1/4"	1.5	75
EXP-EH-5G/45G	EXP-EH-5GS/45GS	850	340	2310	34	1 1/4"	2	75

**NOTE:** The above models are available with insulation only (no heating) - see description for model numbers.

**ALSO:** The above models are available with extra trace tape heating in the top section suitable for extremely cold climates (Arctic version EXP-AH-(model No.)).