

AS2000HAT PROTECTIVE FACE SHIELD

12-20 CAL/CM² WEIGHT BALANCING ARC FLASH PROTECTION FACE SHIELD


AS2000HAT - Salisbury by Honeywell's NEW revolutionary AS2000HAT is a Weight Balancing Arc Flash Protection Face Shield. The shield stows in a balanced, compact position, centered over the top of the hard hat when not in use. The AS2000HAT has an ATPV rating of 20 cal/cm² and utilizes nanotechnology to provide a clearer, more transparent window for improved visibility. The face shield unit includes ventilation ribs that allow a natural convection air flow through the top of the face shield. This reduces fogging of the visor, lowers CO₂ levels and improves comfort.



AS2000HAT SERIES

- 7.5" x 20" Viewing area
- Extra light tint
- .06" Thick
- Absorbs >99.9% of harmful UV radiation
- Resistant to fogging
- Meets current ANSI Z87.1 and is CSA standard compliant
- Tested to ASTM F2178 specifications

AS1200HAT - Salisbury by Honeywell's revolutionary AS1200HAT is a Weight Balancing Arc Flash Protection Face Shield, that stows in a balanced, compact position, centered over the top of the hard hat when not needed. The AS1200HAT has an ATPV rating of 12 cal/cm² and utilizes nanotechnology to provide a more transparent window for improved visibility. The shield/window is designed to be easily replaced without tools. The face shield unit includes ventilation ribs that allow a natural convection air flow through the top of the face shield. This reduces fogging of the visor, lowers CO₂ levels and improves comfort for the user.



AS1200 SERIES

- 7.5" x 20" Viewing area
- Extra light tint
- .06" Thick
- Absorbs >99.9% of harmful UV radiation
- Resistant to fogging
- Meets current ANSI Z87.1 and is CSA standard compliant
- Tested to ASTM F2178 specifications



CAT. NO.	DESCRIPTION
AS2000HAT	20 cal/cm ² , arc flash protection face shield unit w/SA79R03 hard hat
AS2000HAT-CLR	20 cal/cm ² , arc flash protection face shield unit w/SA79R03 hard hat and transparent chin guard
AS2000	20 cal/cm ² , arc flash protection face shield unit
AS2000FB	20 cal/cm ² , arc flash protection face shield unit for full brim hard hats
AS2000FS	Replacement face shield/window
AS1200HAT	12 cal/cm ² weight balancing arc flash protection face shield unit w/hard hat
AS1200HAT-CLR	AS1200HAT w/ transparent chin guard
AS1200PPC	12 cal/cm ² weight balancing arc flash protection face shield unit. Made of Premium Polycarbonate with permanent anti-fog/anti-scratch coating
AS1200CLR-PPC	12 cal/cm ² weight balancing arc flash protection face shield unit with transparent chin protector. Made of Premium Polycarbonate with permanent anti-fog/anti-scratch coating
AS1200	12 cal/cm ² weight balancing arc flash protection face shield unit.



NOTE: IN ORDER TO ACHIEVE 360 DEGREE 20 CAL/CM² PROTECTION, A 20 CAL/CM² BALACLAVA MUST BE WORN.

NFPA 70E: AN ARC RATED HOOD SHALL BE USED WHEN THE ANTICIPATED INCIDENT ENERGY EXPOSURE EXCEEDS 12 CAL/CM².