LOW VOLTAGE MOLDED SLEEVES & ACCESSORIES

MOLDED SLEEVES are manufactured by either injection or compression molding methods. The advantage these methods offer is the ability to produce sleeves of Type I or SALCOR® Type II synthetic rubber. SALCOR® sleeves provide the same high quality and electrical protection as natural rubber, with the added benefit of being resistant to ozone and ultraviolet radiation. Type I sleeves are available in black, yellow or maroon. Type II SALCOR® sleeves are black or orange. Molded sleeves are available in curved arm style only.

PROPER STORAGE EXTENDS THE SERVICE LIFE OF

MOLDED SLEEVES. Folds and creases strain rubber and cause it to crack from ozone prematurely. By storing rubber sleeves in the right size bag, and never forcing more than one pair into each bag, equipment will lie flat and extend the life of the product. Salisbury bags are constructed of heavy duty canvas duck and are double stitched and riveted at stress points for extra durability. Canvas bags feature a D ring for hanging in trucks or on work belts. Bags feature tapered gussets with wide opening tops for easy insertion.

SLEEVE BUTTONS, STRAPS AND HARNESSES are required to wear rubber insulating sleeves properly. Four buttons are required per pair of sleeves. Two straps are required per pair of sleeves. One harness is required per pair of sleeves.

CAT. NO. BREAKDOWN FOR MOLDED TYPE I SLEEVES

VOLTAGE CLASS	SIZE	COLOR
1	R or L	Y
2	R, L or XL	В, Ү, М
3	R or L	Y, M
4	R or L	М
R=Regular L=Large XL=Extra Large Example: 2LB		B=Black Y=Yellow M=Maroon

CAT. NO. BREAKDOWN FOR MOLDED TYPE II SLEEVES

VOLTAGE CLASS	SIZE	COLOR
1	R or L	BS or OS
2	R, L or XL	BS or OS
R=Regular L=Large Example: 2LOS	XL=Extra Large	BS=Black SALCOR OS=Orange SALCOR

CAT. NO.	FOR SLEEVE LENGTH in. (mm	DIMENSIONS inches (mm)	WEIGHT EA. Ibs. (kgs)		
CANVAS SLEEVE BAG					
T31	—	30" x 9.5" (762 x 241mm)	1.5 (. 7)		
T32	_	30" x 13" (762 x 330 mm)	3 (1.4)		
BUTTONS					
B2	_	One Piece Sleeve Button	.2 (.01)		
B22	_	4 Screw Type Buttons	.8 (.04)		
STRAPS					
S1	1	5"(381mm) Strap w/ 4 B2 Buttons	.1 (.005)		
HARNESS					
H1		Harness w/ 4 B2 Buttons	1 (.45)		





